

RAMI254EXT-LB5

LOUD AND CLEAR

PRODUCT DESCRIPTION

Rockwell Collins Part Number 013-2071-190
RAMI Part Number RAMI254EXT-LB5
NSN 5985-01-673-9259
Market Military -Land

The RAMI254EXT-LB5 is a replacement for the OE-254/GRC Antenna Group. It is comprised of fewer piece parts, allowing for quicker assembly and erection, along with being capable of VHF, UHF and L-Band operation modes. It can be deployed atop its 27 ft. mast (RAMI5008-FG) or utilized on the ground standing on its tripod base. It is manufactured to meet the mechanical and environmental specifications as called out in MIL-PRF-49204 (OE-254/GRC specification). The antenna comes complete with a 100 ft. LMR-400 transmission line with an in-line adapter (antenna to triplexer) and three 5 ft. RG-223 transmission lines (triplexer to radio set). Additional components for full assembly and erection (mast to ground deployment) are sold separately.



Application Ground Based Communications

Frequency 30-88 MHz

225-450 MHz 1200-2110 MHz

Impedance 50 Ohms Nominal

VSWR 30-88 MHz: 3.0:1 Max. 225-450 MHz: 3.0:1 Max.

225-450 MHz: 3.0:1 Max. 1200-2110 MHz: 2.75:1 Max.

Isolation 40 dB

Polarization Vertical

Pattern Omni-Directional

Connector "N" Female at antenna feed point

"N" Male at Radio Set

RF Power VHF 75 Watts CW Handling UHF 75 Watts CW


L-BAND 75 Watts CW


Gain 30-88 MHz -5.0 dBi to 0.0 dBi

225-450 MHz 0.0 dBi to +2.0 dBi

1200-2110 MHz +1.0 dBi 1250-1350 MHz +3.0 dBi 1750-1850 MHz +3.0 dBi

Color P/N: RAMI254EXT-LB5G CARC Green











RAMI254EXT-LB5

LOUD AND CLEAR







CABLE W/DIPLEXER P/N: LB5-501A-CA QTY.: 1



TECHNICAL MANUAL P/N: 27-LB6 QTY.: 1

INSULATING TAPE P/N: 944763 QTY.: 1

